



www.telecomtender.com



Product.

ردیف ۱

1/2" Jumper , N-male/ N-male

Prod No.

FCCC-301002

Application and Properties:

Jumpers are commonly used for the connection of the RF cable lines with the antenna or with the radios. Cable and connectors have been soldered together in the production operation. Security of the joint and their concentric is guaranteed by a tight plastic cover. this flexible jumper designed, manufactured and/or distributed under this quality management system (ISO9001 & ISO14001). Quality of the product is tested according to IEC and MIL Standards.

- Other Details

- High quality and excellent performances
- Low attenuation and VSWR
- 1/2" super flexible coaxial cable (length of cable depending on customer request)
- Flexible
- Degree of protection: IP 68 compliant with IEC 60529
- High reliability, safety, UV protected
- Optimized to provide high performance in telecommunication networks
- Fast installation without the need for any additional expensive tools
- Compliant with MIL, IEC and RoHS



- Technical Specification

General specifications	
Cable	1/2 " Superflexible, UV Protected
Jumper Type	Factory-Fit (Standard)
Length	1m, & according to request of customer
Connector A	N male/Straight
Connector B	N male/Straight
Electrical data	
Characteristic Impedance	50±1 Ω
3rd Order IMD	≥160 dBc
Insulation Resistance	≥ 100000 MΩ
DC Breakdown Voltage (4kV,A.C.,1min)	No Breakdown or Flashover
VSWR	DC-3700 MHz < 1.1
Mechanical & Environmental data	
Minimum Bending Radius	25 mm
Degree of protection	IP68, IEC 60529
Working Temperatre	-40 C to +85 C